

TANEJA GREAT GROUP OF INDUSTRIES

www.greatyuva.com

DC INVERTER MMA WELDER

Features

- With good protection of under voltage, over voltage and over current, it makes the machine safe and reliable.
- ◆ Self-adaptive power switch, wide range from 110 Volt to 280 Volt for single phase.
- ◆ CC feature, with sable arc.
- ◆ Original imported New Generation IGBT, with high stability.
- ◆ With advanced high efficiency inverter technique 30KHz, high frequency, energy saving and environmental protection.
- ◆ Effectively solved the problem of unstable power supply by using generator during outdoor work.





Main Technical Parameters :	YUVA-200NW
nput voltage (V)	AC220V <u>+</u> 10%
requency (Hz)	50/60
ated input current (A)	23
lo-load voltage (V)	65
Output current range (A)	40-200
Output voltage range (V)	20.8-26.4V
outy cycle (%)	60% 170A
fficiency (%)	80%
ower factor	0.73
sulation class	F
ase protect class	IP21
mension (L*W*H)(mm)	250X125X225
/eight (KG)	4







- 1.8 meter 16mm2 welding cable with electrode holder
- 1.2 meter 16mm2 earth cable with 100A earth clamp

TANEJA GREAT INDUSTRIES LLP

Office: A-32 Naraina Industrial Area, Phase-1, New Delhi - 110028. Toll Free no:- 18002576004

Email: taneja@greatyuva.com, greatcab@yahoo.com Website: www.greatyuva.com