

Professional double IGBT model



Features

- ◆ With good protection of under voltage, over voltage and over current, it makes machine safe and reliable
- ◆ Pre-set precise digital voltage/current data, easy operation
- ◆ Double IGBT high power module, high efficiency and energy saving
- ◆ High voltage slow wire feeding arc starting, no explode wire, removing tip ball at arc ending
- ◆ With CC/CV function, one machine with MIG/MMA/Lift TIG
- ◆ With 2T/4T working mode, convenient operation
- ◆ Special feature for vertical / horizontal welding
- ◆ Special feature for using flux cored wire
- ◆ Independent adjust arc ending data, easier operation
- ◆ With three proof industry design, using life long, working stable and reliable in kinds of adverse circumstances.



Main Technical Parameter

YMIG-600PR

	MIG	MMA
Input Voltage (V)	AC415V±10%	
Frequency (Hz)	50/60	
Rated input capacity (KVA)	24	26
Rated input current (A)	33.3	36
No-load voltage (V)	70	
Max output current (A)	600	
Output voltage range (V)	16V-39V	22.4V-40V
Duty cycle (%)	60%	
Output current range (A)	60-600	
Insulation class	F	
Case protect class	IP21S	
Dimension (L*W*H)(mm)	625X302X585	
Weight (KG)	31	
Suitable wire (mm)	1.0/1.2/1.6	
Feeding speed (m/min)	3--24	
Gas flow (L/min)	8-25	



Accessories



- Wire Feeder
- CO₂ Regulator With Pre Heater & Flowmeter
- Welding Torch
- Earthing Cable Assembly

★ Wire Feeder with 4 Roll Drive

Office : A-32 Naraina Industrial Area, Phase-1, New Delhi - 110028. Toll Free no:- 18002576004

Email : taneja@greatyuva.com, greatcab@yahoo.com Website : www.greatyuva.com