

CUT Series (IGBT) Inverter DC AIR Plasma Cutter

CUT 200CNC

















Standard Accessories

- 1 pc XF-300 water cooled straight torch (8m)
- 1 set earth clamp with 35mm2 cable (2m)
- 1 set Water cooling unit 10L
- 1 set water pipe (red and blue)



MANUFACTURER / IMPORTER IN INDIA

SALES: SALES@VIRGOPLUS.IN SERVICES:- SUPPORT@VIRGOPLUS.IN

VIRGO SOLUTIONS INDIA LLP

AHMEDABAD, AURANGABAD, BHUBANESWAR, DELHI, GUWAHATI, HYDERABAD, INDORE, JAIPUR, KOLKATA, LUCKNOW, LUDHIANA, MUMBAI, NAGPUR, PUNE, RAIPUR, VARANASI



Product description:

- With good protection of under voltage, over voltage and over current it makes machine safe and reliable.
- Industrial type, heavy duty; easy moving.
- Suitable for both manual & automatic cutting (CNC compatible).
- Exact digital current preset, it makes machine be easy operated.
- With 2T/4T working mode, convenient operation.
- Advanced IGBT inverter technology, high working frequency, high working efficiency and energy saving.
- High frequency and high pressure arc striking, 100% arc starting.
- Advanced air flow control system, it has a save of 30% air compare to traditional machine, which prolongs the using life of air compressor.
- With self-lock working mode, it reduces the working intensity greatly.
- With tri-proof design, it ensures working stable and reliable when in kinds of adverse circumstances.
- Can be used for carbon steel, stainless steel, galvanised steel, copper, aluminium and other metal sheet cutting.

Main technical parameters:

	CUT 200CNC
Input voltage	3-415V+15%
Frequency	50/60Hz
Rated input capacity	40 KVA
Rated input current	54.9A
Rated load voltage	315V
Cutting current adjustment range	40-200A
Maximum cutting thickness	55
Gas Pressure	0.4-0.6
Current slow rise time	0.1-0.2
Arc pressure output signal	1:1/1:20 ARC Voltage
Rated duty cycle (%)	100%
Insulation Class	F
Shell protection grade	IP21S
Weight (kg)	75kg
Dimensions in mm	780X365X800