

TIG Series (Mosfet) DC TIG/MMA Welder

TIG - 200 A















Standard Accessories

- 1 pc WP-17 TIG torch (4m)
- 1 set earth clamp with 16mm2 cable (2m) + 10-25 male connector
- 1 pc long cap, short cap
- 1 pc collet body 2.4, collet 1.6/2.0/2.4
- 1pc alumina nozzle #4/#5/#6



MANUFACTURER / IMPORTER IN INDIA

SALES: SALES@VIRGOPLUS.IN SERVICES: SUPPORT@VIRGOPLUS.IN

VIRGO SOLUTIONS INDIA LLP

AHMEDABAD, AURANGABAD, BHUBANESWAR, DELHI, GUWAHATI, HYDERABAD, INDORE, JAIPUR, KOLKATA, LUCKNOW, LUDHIANA, MUMBAI, NAGPUR, PUNE, RAIPUR, VARANASI



Product description:

- Adopting advanced inverter technology, high working efficiency, small in size and light in weight and portable
- One machine with TIG / MMA welding
- Protection equipment is set internally to prevent over heat, over current, lack of voltage etc. to ensure safe operation
- Original imported inverter components, energy saving
- High capacity fast recovery diode, strong anti-interference
- High frequency arc starting, easy striking at 8 Amps
- Reasonable structure technology, reliable and durable, easy for maintenance.
- Adopt advance cooling technology, more efficient and more stable than traditional machines.
- Suitable for materials like low carbon steel, medium carbon steel and alloy steel, continuous welding and beautiful welding seam.
- With tri-proof design and suitable in kinds of adverse circumstances.

Main technical parameters:

	TIG - 200 A
Input power voltage (V)	AC230V ‡ 10%
Frequency (Hz)	50/60
Rated input current (A)	TIG. 18 8 MMA: 30
Rated output voltage (V)	TIG: 17.2 MMA: 27.2
No-load voltage (V)	65
Current adjusting range	8-200
Duty cycle (%)	60%
Efficiency (%)	87%
Power factor	0.73
Insulation class	F
Case protection degree	IP21
Weight (kg)	8
Dimensions in mm	365X150X290